xcite LED Lighting

Data Sheet



Order Code: XCEMBANM3ST

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintainted Emergency Self-test

Features



- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

Construction

- · Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance

















General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.03
Weight (kg)	0.51	Power Factor (pf)	0.17
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
LED		Conductor Size (mm)	1.5
	70	Terminal Type	2 note niene key
Macadam Elipses	2.1		
Driver			
Driver Current (mA)	360		
Forward Voltage (V)	3.4		
Emergency			
Emergency Lumen Operating	190		
Emergency Wattage (W)	1		

xcite LED Lighting

Data Sheet



Order Code: XCEMBANM3ST

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintainted Emergency Self-test

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

