xcite LED Lighting

Data Sheet



Order Code: XCEMBANM3ST

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintainted Emergency Self-test

Features



- · 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- · Supplied with LiFePO4 battery

Construction

- · Polycarbonate body and diffuser
- Maintained or non-maintained available
- · Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance

















100.11.100.11.2.01.01				
General		Electrical		
Luminaire Wattage (W)	1	Rated Input Current (A)	0.03	
Weight (kg)	0.51	Power Factor (pf)	0.17	
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240	
LED		Conductor Size (mm)	1.5	
LED CRI	70	Terminal Type	3 pole piano key	
Macadam Elipses	2.1			
Driver				
Driver Current (mA)	360			
Forward Voltage (V)	3.4			
Emergency				
Emergency Lumen Operating	190			
Emergency Wattage (W)	1			



xcite LED Lighting

Data Sheet



Order Code: XCEMBANM3ST

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintainted Emergency Self-test

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

