xcite LED Lighting

Data Sheet



0.053 0.44 220-240 1.5

4 pole piano key

Order Code: XCEMBM3

1W - Emergency Bulkhead - 3hrs Maintained Emergency



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Reduced maintenance and high performance
- Semi recessed bezel available
- Polycarbonate body and diffuser

Construction

- Maintained or non-maintained available
- Supplied with self adhesive universal EURO 4 legend
- Supplied as standard with daylight [6500K] LED















Technical Data

General		Electrical
Luminaire Wattage (W)	3	Rated Input Current (A)
Weight (kg)	0.56	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output Lumens (Im)		Conductor Size (mm)
	150	Terminal Type
LED		
CCT (K)	6500	
CRI	70	
Emergency		
Emergency Lumen Operating	150	
Emergency Wattage (W)	1	



xcite LED Lighting

Data Sheet



Order Code: XCEMBM3

1W - Emergency Bulkhead - 3hrs Maintained Emergency

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing



