xcite LED Lighting

Data Sheet



Order Code: XCEMBM3ST

3W - Fixed output - Emergency Self-test - 6500K



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance

Construction

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance















Technical Data

General		
Luminaire Wattage (W)	3	Rated Input
Weight (kg)	0.56	Power Facto
Operating Temperature (ta °C)	5 to 25	Input Voltage
Light Output		Conductor S
Lumens (Im)	200	Terminal Typ
Efficacy (lm/W)	70	
LED		
CCT (K)	6500	
CRI	70	
Driver		
Forward Voltage (V)	3.4	
Emergency		
Emergency Lumen Operating	140	
Emergency Wattage (W)	3	

Electrical		
Rated Input Current (A)	0.053	
Power Factor (pf)	0.44	
Input Voltage Range (VAC)	220-240	
Conductor Size (mm)	1.5	
Terminal Type	4 pole piano key	



xcite LED Lighting

Data Sheet



Order Code: XCEMBM3ST

3W - Fixed output - Emergency Self-test - 6500K

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing



