

**Order Code: XCEMBM3ST**

3W - Fixed output - Emergency Self-test - 6500K



**Features**

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance

**Construction**

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance, includes a disable function



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	3	Rated Input Current (A)	0.053
Weight (kg)	0.56	Power Factor (pf)	0.44
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Conductor Size (mm)	1.5
		Terminal Type	4 pole piano key
Lumens (lm)	200		
Efficacy (lm/W)	70		
LED			
CCT (K)	6500		
CRI	70		
Driver			
Forward Voltage (V)	3.4		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	3		

**Order Code: XCEMBM3ST**

3W - Fixed output - Emergency Self-test - 6500K

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

