xcite LED Lighting

Data Sheet



Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Polycarbonate body and diffuser

Construction

- Maintained or non-maintained available
- Supplied with self adhesive universal EURO 4 legend
- Supplied as standard with daylight [6500K] LED













Technical Data

General		
Luminaire Wattage (W)	1	Rated Input Curren
Weight (kg)	0.55	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Rang
Light Output Lumens (lm)		Conductor Size (mi
	150	Terminal Type
LED		
CCT (K)	6500	
CRI	70	
Emergency		
Emergency Lumen Operating	150	
Emergency Wattage (W)	1	

Electrical	
Rated Input Current (A)	0.031
Power Factor (pf)	0.17
Input Voltage Range (VAC)	220-240
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key



xcite LED Lighting

Data Sheet



Order Code: XCEMBNM3

1W - Emergency Bulkhead - 3hrs Non-Maintained Emergency

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing



