

Order Code: XCFC10CT

10W - Floodlight - CCTK Selector - [3000K/4000K/6000K]



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT selectable via selector switch [3000K/4000K/6000K]
- Available in 4 different outputs
- Available with high performance PIR
- Available with microwave sensor + photocell only function (via the remote, supplied as standard)
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80

Technical Data

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.0422
Weight (kg)	0.55	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 40	Input Voltage Range (VAC)	220-240
Light Output		Terminal Type	3 pole screw down
Lumens (lm)	1000		
Efficacy (lm/W)	100		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	>80		
Macadam Elipses	<5		

Order Code: XCFC10CT

10W - Floodlight - CCTK Selector - [3000K/4000K/6000K]

Dimensions

A (mm)	164
B (mm)	129
C (mm)	39

Line Drawing

