

**Order Code: XCFC10CTP**

10W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Available with high performance PIR or microwave detector
- Available in 4 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 100 lumens per watt efficacy

**Construction**

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.0504
Weight (kg)	0.62	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 40	Input Voltage Range (VAC)	220-240
<b>Light Output</b>		Terminal Type	3 pole screw down
Lumens (lm)	1000		
Efficacy (lm/W)	100		
<b>LED</b>			
CCT (K)	3000K/4000K/6000K		
CRI	>80		
Macadam Elipses	<5		

**Order Code:** XCFC10CTP

10W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]

### Dimensions

A (mm)	164
B (mm)	170
C (mm)	51

### Line Drawing

