

Order Code: XCFC30CTMS

30W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Available in 4 different outputs
- Available with high performance PIR or microwave sensor with PC only function
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 117 lumens per watt efficacy

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|-------------------|
| Luminaire Wattage (W) | 30 | Rated Input Current (A) | 0.1361 |
| Weight (kg) | 1.00 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | -20 to 40 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Terminal Type | 3 pole screw down |
| Lumens (lm) | 3500 | | |
| Efficacy (lm/W) | 117 | | |
| LED | | | |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | >80 | | |
| Macadam Elipses | <5 | | |

Order Code: XCFC30CTMS

30W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]

Dimensions

| | |
|--------|-----|
| A (mm) | 237 |
| B (mm) | 186 |
| C (mm) | 39 |

Line Drawing

