

Order Code: XCFC30CTMS

30W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Available with high performance PIR or microwave detector
- Available in 4 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 117 lumens per watt efficacy

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80



Technical Data

General	
Luminaire Wattage (W)	30
Weight (kg)	1.00
Operating Temperature (ta °C)	-20 to 40

Light Output	
Lumens (lm)	3500
Efficacy (lm/W)	117

LED	
CCT (K)	TRI-COLOUR
CRI	>80
Macadam Ellipses	<5

Electrical	
Rated Input Current (A)	0.1361
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Type	3 pole screw down

Order Code: XCFC30CTMS

30W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]

Dimensions

A (mm)	237
B (mm)	186
C (mm)	39

Line Drawing

