xcite LED Lighting

Data Sheet



Order Code: XCFC50CTMS

50W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- · Available in 4 different outputs
- Available with high performance PIR or microwave detector
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 110 lumens per watt efficacy

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80















Technical Data

General		
Luminaire Wattage (W)	50	
Weight (kg)	1.00	
	-20 to 40	
Light Output		
Lumens (lm)	5500	
Efficacy (lm/W)	110	
LED		
CCT (K)	TRI-COLOUR	
CRI	>80	
Macadam Elipses	<5	

Electrical		
Rated Input Current (A)	0.214	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	220-240	
Terminal Type	3 pole screw down	



xcite LED Lighting

Data Sheet



Order Code: XCFC50CTMS

50W - Floodlight with Microwave Sensor - CCTK Selector [3000K/4000K/6000K]

Dimensions

A (mm)	237
B (mm)	186
C (mm)	39

Line Drawing



