# xcite LED Lighting

## **Data Sheet**

Order Code: XCFC50CTP

50W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]





- · Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- · Available in 4 different outputs
- Available with high performance PIR or microwave detector
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface
- Up to 110 lumens per watt efficacy

#### Construction

- Die-cast aluminium body finished with black marine grade paint
- Weatherproof IP65 construction
- CRI: Ra>80















### **Technical Data**

General	
Luminaire Wattage (W)	50
Weight (kg)	1.05
	-20 to 40
Light Output	
Lumens (Im)	5500
Efficacy (lm/W)	110
LED	
CCT (K)	TRI-COLOUR
CRI	>80
Macadam Elipses	<5

Electrical	
Rated Input Current (A)	0.2161
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Terminal Tyne	3 nole screw down

## xcite LED Lighting

## **Data Sheet**



Order Code: XCFC50CTP

50W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]

#### **Dimensions**

A (mm)	237
B (mm)	233
C (mm)	53

### Line Drawing



