

**Order Code: XCFC50CTP**

50W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Available in 4 different outputs
- Available with high performance PIR or microwave sensor with PC only function
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 110 lumens per watt efficacy

**Construction**

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	50	Rated Input Current (A)	0.2161
Weight (kg)	1.05	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 40	Input Voltage Range (VAC)	220-240
		Terminal Type	3 pole screw down
Light Output			
Lumens (lm)	5500		
Efficacy (lm/W)	110		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	>80		
Macadam Elipses	<5		

**Order Code:** XCFC50CTP

50W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]

### Dimensions

A (mm)	237
B (mm)	233
C (mm)	53

### Line Drawing

