

Order Code: XCFRA5CTSN

5W - Fire Rated Recessed Mini Downlight - CCTK selector [3000K/4000K/6000K] - Satin Nickel



Features

- Compact fire rated downlight with AC on board driver technology
- CCT selectable via selector switch [3000K/4000K/6000K]
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [[Compatibility Matrix](#)]
- Up to 90 lumens per watt efficacy

Construction

- Loop in/out mains connections with easy-fit connector
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- White, Satin Nickel or Polished Chrome Finish



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|------------------|
| Luminaire Wattage (W) | 5 | Rated Input Current (A) | 0.014 |
| Weight (kg) | 0.15 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 5 |
| Light Output | | Surge Protection (kV) | 1 |
| Lumens (lm) | 400 to 500 | Conductor Size (mm) | 2.5 |
| Efficacy (lm/W) | 90 | Terminal Type | 3 pole piano key |
| LED | | | |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |

Order Code: XCFRA5CTSN

5W - Fire Rated Recessed Mini Downlight - CCTK selector [3000K/4000K/6000K] - Satin Nickel

Dimensions

| | |
|--------------|-------|
| C (mm) | 57 |
| ----- | ----- |
| Cut Out (mm) | 60 |
| ----- | ----- |
| Dia. (mm) | 80 |
| ----- | ----- |

Line Drawing

