

Order Code: XCFRA5CTW

5W - Fire Rated Recessed Mini Downlight - CCTK selector [3000K/4000K/6000K] - White



Features

- Compact fire rated downlight with AC on board driver technology
- CCT selectable via selector switch [3000K/4000K/6000K]
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [[Compatibility Matrix](#)]
- Up to 90 lumens per watt efficacy

Construction

- Loop in/out mains connections with easy-fit connector
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- White, Satin Nickel or Polished Chrome Finish



Technical Data

General		Electrical	
Luminaire Wattage (W)	5	Rated Input Current (A)	0.014
Weight (kg)	0.15	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	5
Light Output		Surge Protection (kV)	1
Lumens (lm)	400 to 500	Conductor Size (mm)	2.5
Efficacy (lm/W)	90	Terminal Type	3 pole piano key
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	4		

Order Code: XCFRA5CTW

5W - Fire Rated Recessed Mini Downlight - CCTK selector [3000K/4000K/6000K] - White

Dimensions

C (mm)	57
-----	-----
Cut Out (mm)	60
-----	-----
Dia. (mm)	80
-----	-----

Line Drawing

