

Order Code: XCFRA5WWPC

5W - Fire Rated Recessed Mini Downlight - 3000K - Polished Chrome



Features

- Compact fire rated downlight with AC on board driver technology
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [[Compatibility Matrix](#)]
- Up to 80 lumens per watt efficacy

Construction

- Loop in/out mains connections with integrated driver
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- White, Matt White, Satin Nickel or Polished Chrome Finish
- Available in warm white [3000K] or neutral white [4000K]



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 5 |
| Weight (kg) | 0.13 |
| Operating Temperature (ta °C) | 0 to 25 |

Light Output

| | |
|-----------------|-----|
| Lumens (lm) | 400 |
| Efficacy (lm/W) | 80 |

LED

| | |
|-----------------|------|
| CCT (K) | 3000 |
| CRI | 80 |
| Macadam Elipses | 4 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.014 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 5 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 3 pole piano key |

Order Code: XCFRA5WWPC

5W - Fire Rated Recessed Mini Downlight - 3000K - Polished Chrome

Dimensions

| | |
|--------------|----|
| C (mm) | 80 |
| ----- | |
| Cut Out (mm) | 60 |
| ----- | |
| Dia. (mm) | 80 |
| ----- | |

Line Drawing

