

### Order Code: XCFRA7CT

7W - Fire Rated Recessed Downlight - IP65 - CCTK Selector [3000K/4000K/6000K]



#### Features

- Ideal for retrofit of existing halogen downlight fixtures
- Suitable for domestic applications
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Available in 5 different coloured bezels and 2 sizes [not included]
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30 minute fire rating with Staircraft I-Joist [\[Compatibility Matrix\]](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- Up to 100 lumens per watt efficacy

#### Construction

- Loop in/out mains connections with easy-fit connector



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	7	Rated Input Current (A)	0.03
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
<b>Light Output</b>		Inrush Current Peak (A)	1.04
Lumens (lm)	600 to 700	Surge Protection (kV)	1
Efficacy (lm/W)	100	Conductor Size (mm)	2.5
<b>LED</b>		Terminal Type	3-POLE GRIP-WIRE
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Ellipses	4		
<b>Driver</b>			
Driver Current (mA)	19		
Forward Voltage (V)	260		

**Order Code: XCFRA7CT**

7W - Fire Rated Recessed Downlight - IP65 - CCTK Selector [3000K/4000K/6000K]

Dimensions

C (mm)	60
-----	-----
Cut Out (mm)	62
-----	-----
Dia. (mm)	75
-----	-----

Line Drawing

