xcite LED Lighting

Data Sheet

0.69 0.95 100 - 240

> 350 6

push

Order Code: XCHBA150NW 150W - High Bay - Fixed output - 4000K





- Ideal for retro-fit of SON or Metal Halide high bays
- Available in 2 sizes and 3 outputs
- Suspension via chain or wire suspension
- Suitable for mounting heights between 5m and 12m
- Microwave dimming sensor option available

Construction

- Die-cast aluminium body finished in black
- Integral driver
- Supplied as standard with neutral white [4000K] LED















Technical Data

		reciniic	cai Data	
Luminaire Wattage (W)	General	150	Rated Input Current (A)	Electrical
Weight (kg)		1.91	Power Factor (pf)	
Operating Temperature (ta °C)		-20 to 25	Input Voltage Range (VAC)	
	Light Output		Inrush Current Peak (A)	
Light Output Lumens (Im)		20000	Surge Protection (kV)	
Efficacy (Im/W)		133	Conductor Size (mm)	
	LED		Terminal Type	
CCT (K)		4000		
CRI		80		
Macadam Elipses		<3		
	Driver			
Driver Current (mA)		560		
Forward Voltage (V)		240		



xcite LED Lighting

Data Sheet



Order Code: XCHBA150NW 150W - High Bay - Fixed output - 4000K

Dimensions

C (mm)	112
Dia. (mm)	361

Line Drawing



