xcite LED Lighting

Data Sheet



Order Code: XCHBA150NWMS

150W - High Bay - Microwave sensor - 4000K



Features

- Ideal for retro-fit of SON or Metal Halide high bays
- Available in 2 sizes and 3 outputs
- Suspension via chain or wire suspension
- Suitable for mounting heights between 5m and 12m
- · Microwave dimming sensor option available

Construction

- Die-cast aluminium body finished in black
- Integral driver
- Supplied as standard with neutral white [4000K] LED













Technical Data

General	
Luminaire Wattage (W)	150
Weight (kg)	2.47
	-20 to 25
Light Output	
Lumens (Im)	20000
Efficacy (lm/W)	122
LED	
CCT (K)	4000
CRI	80
Macadam Elipses	<3
Driver	
Driver Current (mA)	560
Forward Voltage (V)	240

Electrical		
Rated Input Current (A)	0.69	
Power Factor (pf)	0.95	
Input Voltage Range (VAC)	100 - 240	
Inrush Current Peak (A)	350	
Surge Protection (kV)	6	
Conductor Size (mm)	1	
Terminal Type	push	



xcite LED Lighting

Data Sheet



Order Code: XCHBA150NWMS

150W - High Bay - Microwave sensor - 4000K

Dimensions

C (mm)	140
Dia. (mm)	361

Line Drawing



