

Order Code: XCHBA200NWMS

200W - High Bay - Microwave sensor - 4000K

Features

- Ideal for retro-fit of SON or Metal Halide high bays
- Available in 2 sizes and 3 outputs
- Suspension via chain or wire suspension
- Suitable for mounting heights between 5m and 12m
- Microwave dimming sensor option available

Construction

- Die-cast aluminium body finished in black
- Integral driver
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	200	Rated Input Current (A)	0.92
Weight (kg)	2.59	Power Factor (pf)	0.95
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100 - 240
		Inrush Current Peak (A)	350
		Surge Protection (kV)	6
		Conductor Size (mm)	1
		Terminal Type	push
Light Output			
Lumens (lm)	26000		
Efficacy (lm/W)	130		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	<3		
Driver			
Driver Current (mA)	750		
Forward Voltage (V)	240		

Order Code: XCHBA200NWMS

200W - High Bay - Microwave sensor - 4000K

Dimensions

C (mm)	140
Dia. (mm)	361

Line Drawing

