# xcite LED Lighting

### **Data Sheet**



Order Code: XCHLA7NWP

7W - Coach Half Lantern - Fixed output - PIR - 4000K



#### **Features**

• Suitable for doorways and entrance areas

#### Construction

- Black polycarbonate body
- Clear polycarbonate diffuser
- Supplied as standard with neutral white [4000K] LED



















### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	7	Power Factor (pf)	0.5
Weight (kg)	0.65	Input Voltage Range (VAC)	220-240V
Operating Temperature (ta °C)	0 to 25	Inrush Current Peak (A)	15
Light Output  Lumens (Im)		Surge Protection (kV)	0.5kV
	400	Conductor Size (mm)	2.5
Efficacy (Im/W)	57	Terminal Type	SCREW
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	70mA		
Forward Voltage (V)	93-115V		

# xcite LED Lighting

### Data Sheet



Order Code: XCHLA7NWP


7W - Coach Half Lantern - Fixed output - PIR - 4000K


#### **Dimensions**

A (mm)	362
B (mm)	176
C (mm)	93

#### Line Drawing

В





С