

Order Code: XCLGP6630DL

30W - Recessed Low Glare Panel - 600m x 600m - 6000K



Features

- Backlit recessed module
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

Construction

- Extruded aluminium frame
- Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]



Technical Data

| General | | Electrical | |
|-------------------------------|----------|---------------------------|------------------|
| Luminaire Wattage (W) | 30 | Rated Input Current (A) | 0.13 |
| Weight (kg) | 1.64 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 40 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 1.5 |
| | | Terminal Type | 2 pole grip wire |
| Light Output | | | |
| Lumens (lm) | 3000 | | |
| Efficacy (lm/W) | 100 | | |
| LED | | | |
| CCT (K) | 6000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 750 | | |
| Forward Voltage (V) | 24 to 42 | | |

Order Code: XCLGP6630DL

30W - Recessed Low Glare Panel - 600m x 600m - 6000K

Dimensions

| | |
|--------|-----|
| A (mm) | 595 |
| B (mm) | 595 |
| C (mm) | 35 |

Line Drawing

