

### Order Code: XCLGP6630NWD

30W - Recessed Low Glare Panel - 600m x 600m - Dimmable - 4000K



#### Features

- Backlit recessed module
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- More consistent and uniform appearance than traditional edge-lit panels or downlights
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

#### Construction

- Extruded aluminium frame
- Plug and play driver
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.13
Weight (kg)	1.64	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	10
		Surge Protection (kV)	1
		Conductor Size (mm)	1.5
		Terminal Type	2 pole grip wire
Light Output			
Lumens (lm)	3000		
Efficacy (lm/W)	100		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	750		
Forward Voltage (V)	24 to 42		

**Order Code: XCLGP6630NWD**

30W - Recessed Low Glare Panel - 600m x 600m - Dimmable - 4000K

Dimensions

A (mm)	595
B (mm)	595
C (mm)	35

Line Drawing

