

**Order Code:** XCLGP66X1

X1 LG PANEL - White- Wattage Selectable - Dimmable - CCT [4000K/5000K/6000K] - Micro-prism diffuser - Fixed output

### Features

- **Low glare TP[a] diffuser**  
Improves visual comfort and helps create a more productive working environment
- **4000K, 5000K and 6000K selectable**  
Provides flexibility to tailor the lighting environment to different spaces and user preferences
- **17W to 27W wattage selectable**  
Allows lumen output to be adjusted from 2300 lm to 3500 lm to suit application requirements
- **141 lm/W efficacy**  
Delivers high performance illumination while helping to reduce energy consumption and running costs

### Construction

- **DALI addressable option**  
Provides individual luminaire control, dimming and scene setting for enhanced lighting flexibility and energy management
- **Sensor option available**  
Supports additional energy savings through occupancy and daylight responsive lighting control
- **Emergency option available**  
Maintains illumination during mains power failure to support safe evacuation of the building

### Installation Notes

Wired via 3-pole terminal connection inside main body



### Technical Data

General		Electrical	
Luminaire Wattage (W)	17W/19W/21W/23W/25W/27W	Rated Input Current (A)	0.8 to 0.12
Weight (kg)	1.79	Power Factor (pf)	0.91 to 0.95
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
<b>Light Output</b>		Inrush Current Peak (A)	22.1
Lumens (lm)	2300 to 3500	Surge Protection (kV)	1kV
Efficacy (lm/W)	141	Conductor Size (mm)	0.5 to 2.5
<b>LED</b>		Terminal Type	2 Push Terminal
CCT (K)	4000K/5000K/6000K		
CRI	80		
Macadam Ellipses	3.1 to 13.1		
<b>Driver</b>			
Driver Current (mA)	450 - 500 / 550 - 600 / 650 - 700		
Forward Voltage (V)	32.4 to 34.2		

**Order Code:** XCLGP66X1

X1 LG PANEL - White- Wattage Selectable - Dimmable - CCT [4000K/5000K/6000K] - Micro-prism diffuser - Fixed output

### Dimensions

A (mm)	595
B (mm)	595
B (mm)	35

### Line Drawing

