xcite LED Lighting

Data Sheet



Order Code: XCLS547CTWD

XCITE LINEAR SUSPENDED CCT XCLS - White - 47W - Dimmable - 3000K/4000K/5000K - Opal diffuser



Features

- · Suitable for offices and schools
- Independently switchable up/down modes with adjustable CCT [3000K/4000K/5000K]
- DALI and push switch dimmable as standard
- Complete with adjustable 1.5m wire suspension and 1.8m power feed
- Up to 123 lumens per watt efficacy

Construction

- · Opal polycarbonate diffuser
- Emergency option available
- · Extruded aluminium body finished in black or white
- Fitted polycarbonate end caps





















Technical Data

General			E
Luminaire Wattage (W)	47	Rated Input Curre	ent (A)
Weight (kg)	5.56	Power Factor (pf)	
0	0 to 25	Input Voltage Range (VAC)	
Light Output Lumens (Im)		Surge Protection	(kV)
	5800	Conductor Size (mm)	
Efficacy (lm/W)	123	Terminal Type	SLK series 4
LED			
CRI	90		
Macadam Elipses	<5		
Driver			
Driver Current (mA)	1050		
Forward Voltage (V)	41		

Electrical		
Rated Input Current (A)	0.21	
Power Factor (pf)	0.98	
Input Voltage Range (VAC)	220 to 240	
Surge Protection (kV)	1	
Conductor Size (mm)	0.5 to 2.5	
Terminal Type SLK series 4 to po	le grip to wire + 2 to pole grip to wire	

xcite LED Lighting

Data Sheet



Order Code: XCLS547CTWD

XCITE LINEAR SUSPENDED CCT XCLS - White - 47W - Dimmable - 3000K/4000K/5000K - Opal diffuser

Dimensions

A (mm)	1500
B (mm)	45
C (mm)	70
Fix	1275

Line Drawing



