

Order Code: XCMF10BDLP

10W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black



Features

- Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 60 lumens per watt efficacy

Construction

- Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W) | 10 | Rated Input Current (A) | 0.465 |
| Weight (kg) | 0.37 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Surge Protection (kV) | 0.5 |
| Lumens (lm) | 600 | Conductor Size (mm) | 1.5 |
| Efficacy (lm/W) | 60 | Terminal Type | 3 pole screw down |
| LED | | | |
| CCT (K) | 6000 | | |
| CRI | 65 | | |
| Macadam Ellipses | 4 | | |

Order Code: XCMF10BDLP

10W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black

Dimensions

| | |
|--------|-----|
| A (mm) | 130 |
| B (mm) | 90 |
| C (mm) | 35 |

Line Drawing

