xcite LED Lighting

Data Sheet



Order Code: XCMF10BWW

10W - Outdoor Mini Flood Slimline - 3000K - Black



Features

- · Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 50 lumens per watt efficacy

Construction

- Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution





Macadam Elipses













Technical Data

General		Electrical	
Luminaire Wattage (W)	10	Rated Input Current (A)	0.465
Weight (kg)	0.37	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	220-240
Light Output Lumens (Im)		Surge Protection (kV)	0.5
	500	Conductor Size (mm)	1.5
Efficacy (lm/W)	50	Terminal Type	3 pole screw down
LED			
CCT (K)	3000		
CRI	65		



xcite LED Lighting

Data Sheet



Order Code: XCMF10BWW

10W - Outdoor Mini Flood Slimline - 3000K - Black

Dimensions

A (mm)	130
B (mm)	90
C (mm)	35

Line Drawing



