

**Order Code: XCMF10WDL**

10W - Outdoor Mini Flood Slimline - 6000K - White



**Features**

- Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 60 lumens per watt efficacy

**Construction**

- Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution



**Technical Data**

| General                       |           | Electrical                |                   |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 10        | Rated Input Current (A)   | 0.465             |
| Weight (kg)                   | 0.37      | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 220-240           |
| <b>Light Output</b>           |           | Surge Protection (kV)     | 0.5               |
| Lumens (lm)                   | 600       | Conductor Size (mm)       | 1.5               |
| Efficacy (lm/W)               | 60        | Terminal Type             | 3 pole screw down |
| <b>LED</b>                    |           |                           |                   |
| CCT (K)                       | 6000      |                           |                   |
| CRI                           | 65        |                           |                   |
| Macadam Ellipses              | 4         |                           |                   |

**Order Code: XCMF10WDL**

10W - Outdoor Mini Flood Slimline - 6000K - White

Dimensions

|        |     |
|--------|-----|
| A (mm) | 130 |
| B (mm) | 90  |
| C (mm) | 35  |

Line Drawing

