

**Order Code: XCMF20BDLP**

20W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black



**Features**

- Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 75 lumens per watt efficacy

**Construction**

- Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	20	Rated Input Current (A)	0.897
Weight (kg)	0.61	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	220-240
Light Output		Surge Protection (kV)	0.5
		Conductor Size (mm)	1.5
Lumens (lm)	1500	Terminal Type	3 pole screw down
Efficacy (lm/W)	75		
<b>LED</b>			
CCT (K)	6000		
CRI	65		
Macadam Ellipses	4		

**Order Code: XCMF20BDLP**

20W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black

Dimensions

A (mm)	180
B (mm)	126
C (mm)	35

Line Drawing

