xcite LED Lighting

Data Sheet



Order Code: XCMF20WDL

20W - Outdoor Mini Flood Slimline - 6000K - White



Features

- · Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 75 lumens per watt efficacy

Construction

- · Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution



CRI

Macadam Elipses















Technical Data

General		Electrical	
Luminaire Wattage (W)	20	Rated Input Current (A)	0.897
Weight (kg)	0.61	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	220-240
Light Output Lumens (Im)		Surge Protection (kV)	0.5
	1500	Conductor Size (mm)	1.5
Efficacy (Im/W)	75	Terminal Type	3 pole screw down
LED			
CCT (K)	6000		

xcite LED Lighting

Data Sheet



Order Code: XCMF20WDL

20W - Outdoor Mini Flood Slimline - 6000K - White

Dimensions

A (mm)	180
B (mm)	126
C (mm)	35

Line Drawing



