

**Order Code:** XCMF30BDLP  
30W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black



Features

- Ideal for retrofit of existing halogen floodlights
- Available in 3 sizes
- Available in 3 different outputs
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass
- Up to 67 lumens per watt efficacy

Construction

- Die-cast aluminium body
- White or black body finish
- Low energy and maintenance free solution



Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Rated Input Current (A)	0.13
Weight (kg)	0.82	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	220-240
Light Output		Surge Protection (kV)	1
Lumens (lm)	2000	Conductor Size (mm)	1.5
Efficacy (lm/W)	67	Terminal Type	3 pole screw down
LED			
CCT (K)	6000		
CRI	65		
Macadam Elipses	4		

**Order Code:** XCMF30BDLP  
30W - Outdoor Mini Flood Slimline - Microwave Sensor - 6000K - Black

Dimensions

A (mm)	210
B (mm)	147
C (mm)	35

Line Drawing

