# xcite LED Lighting
Data Sheet

Order Code: XCMPC

Mini Integral Photocell

Features

- Switch on at 10-16 lux (turn off at <65 lux)
- Small and lightweight module
- Cable length: 156mm

Construction

- Polycarbonate body and diffuser
- High quality polycarbonate construction

3 YRS WARRANTY | IP65

Technical Data

General

Weight (kg)	0.03
Operating Temperature (ta °C)	0 to 25

Electrical

Input Voltage Range (VAC)	220 - 240
Conductor Size (mm)	1

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Generated on: 25/12/2025 5:59pm
Produced by xcite LED Lighting

Order Code: XCMPC

Mini Integral Photocell

Dimensions

A (mm)	34
B (mm)	17
C (mm)	156
D (mm)	40
Cut Out (mm)	10

Line Drawing

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

Generated on: 25/12/2025 5:59pm
Produced by xcite LED Lighting