xcite LED Lighting

Data Sheet



0.14 0.98 198-264 20.02 2.5

4 pole piano key

Order Code: XCNC14HENWHFSM3

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K





- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]





















Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical
Luminaire Wattage (W)	32	Rated Input Current (A)
Weight (kg)	1.93	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
1110		Inrush Current Peak (A)
Light Output	5000	Conductor Size (mm)
Lumens (Im)		Terminal Type
Efficacy (lm/W)	156	
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	2	
Driver		
Driver Current (mA)	700mA	
Forward Voltage (V)	24-42	
Emergency		
Emergency Lumen Operating	160	
Emergency Wattage (W)	1	

xcite LED Lighting

Data Sheet



Order Code: XCNC14HENWHFSM3

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1260
B (mm)	98
C (mm)	93

Line Drawing





