

**Order Code: XCNC14HENWM3**

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K



**Features**

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

**Construction**

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

**Technical Data**

**General**

|                               |         |
|-------------------------------|---------|
| Luminaire Wattage (W)         | 32      |
| Weight (kg)                   | 1.83    |
| Operating Temperature (ta °C) | 5 to 25 |

**Light Output**

|                 |      |
|-----------------|------|
| Lumens (lm)     | 5000 |
| Efficacy (lm/W) | 156  |

**LED**

|                  |      |
|------------------|------|
| CCT (K)          | 4000 |
| CRI              | 80   |
| Macadam Ellipses | 2    |

**Driver**

|                     |       |
|---------------------|-------|
| Driver Current (mA) | 700mA |
| Forward Voltage (V) | 24-42 |

**Emergency**

|                           |     |
|---------------------------|-----|
| Emergency Lumen Operating | 160 |
| Emergency Wattage (W)     | 1   |

**Electrical**

|                           |                  |
|---------------------------|------------------|
| Rated Input Current (A)   | 0.14             |
| Power Factor (pf)         | 0.98             |
| Input Voltage Range (VAC) | 198-264          |
| Inrush Current Peak (A)   | 20.02            |
| Conductor Size (mm)       | 2.5              |
| Terminal Type             | 4 pole piano key |

**Order Code: XCNC14HENWM3**

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

|        |      |
|--------|------|
| A (mm) | 1260 |
| B (mm) | 98   |
| C (mm) | 93   |

Line Drawing

