xcite LED Lighting

Data Sheet



Order Code: XCNC14HENWM3


32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Features

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 156 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

























Technical Data

Technical Bata				
General		Electrical		
Luminaire Wattage (W)	32	Rated Input Current (A)	0.14	
Weight (kg)	1.83	Power Factor (pf)	0.98	
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	198-264	
Light Output Lumens (Im)		Inrush Current Peak (A)	20.02	
	5000	Conductor Size (mm)	2.5	
Efficacy (lm/W)	156	Terminal Type	4 pole piano key	
LED				
ССТ (К)	4000			
CRI	80			
Macadam Elipses	2			
Driver				
Driver Current (mA)	700mA			
Forward Voltage (V)	24-42			
Emergency				
Emergency Lumen Operating	160			
Emergency Wattage (W)	1			



xcite LED Lighting

Data Sheet



Order Code: XCNC14HENWM3

32W - 1200mm Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1260
B (mm)	98
C (mm)	93

Line Drawing

