

## Order Code: XCNC15HENW

51W - 1500mm Non Corrosive Polycarbonate Luminaires - IP65 - 4000K



## Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 137 lumens per watt efficacy

## Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

## Technical Data

## General

Luminaire Wattage (W)	51
Weight (kg)	2.24
Operating Temperature (ta °C)	-20 to 25

## Light Output

Lumens (lm)	7000
Efficacy (lm/W)	137

## Electrical

Rated Input Current (A)	0.23
Power Factor (pf)	0.97
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	33.1
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

## LED

CCT (K)	4000
CRI	80
Macadam Ellipses	2

## Driver

Driver Current (mA)	1150mA
Forward Voltage (V)	28-52

**Order Code: XCNC15HENW**

51W - 1500mm Non Corrosive Polycarbonate Luminaires - IP65 - 4000K

## Dimensions

A (mm)	1560
B (mm)	98
C (mm)	93

## Line Drawing

