## xcite LED Lighting

### **Data Sheet**



0.1 0.98 198-264 20.02 2.5

3 pole piano key

Order Code: XCNC15NW

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K






- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 144 lumens per watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips

any similar chemicals.

- Supplied with neutral white [4000K]
- CRI: Ra>80

























| General                       |           | Electrical                |
|-------------------------------|-----------|---------------------------|
| Luminaire Wattage (W)         | 32        | Rated Input Current (A)   |
| Weight (kg)                   | 2.24      | Power Factor (pf)         |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) |
| Light Output Lumens (Im)      |           | Inrush Current Peak (A)   |
|                               | 4300      | Conductor Size (mm)       |
| Efficacy (Im/W)               | 144       | Terminal Type             |
| LED                           |           |                           |
| CCT (K)                       | 4000      |                           |
| CRI                           | 80        |                           |
| Macadam Elipses               | 3         |                           |
| Driver                        |           |                           |
| Driver Current (mA)           | 700mA     |                           |
| Forward Voltage (V)           | 24-42     |                           |

# xcite LED Lighting

### **Data Sheet**



Order Code: XCNC15NW

32W - 1500mm Non Corrosive Polycarbonate Luminaire - IP65 - 4000K

#### **Dimensions**

| A (mm) | 1560 |
|--------|------|
| B (mm) | 98   |
| C (mm) | 93   |

### Line Drawing

