

### Order Code: XCNC16HENWHFSM3

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

#### Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 140 lumens per watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



#### Technical Data

##### General

Luminaire Wattage (W)	63
Weight (kg)	3.07
Operating Temperature (ta °C)	5 to 25

##### Light Output

Lumens (lm)	8800
Efficacy (lm/W)	140

##### LED

CCT (K)	4000
CRI	80
Macadam Elipses	3

##### Driver

Driver Current (mA)	1400mA
Forward Voltage (V)	24-42

##### Emergency

Emergency Lumen Operating	160
Emergency Wattage (W)	1

##### Electrical

Rated Input Current (A)	0.28
Power Factor (pf)	0.98
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	33.1
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key

**Order Code: XCNC16HENWHFSM3**

63W - 1800mm Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1830
B (mm)	100
C (mm)	101

Line Drawing

