

Order Code: XCNC24NWHFS

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 3 lengths
- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

Technical Data

General		Electrical	
Luminaire Wattage (W)	42	Rated Input Current (A)	0.19
Weight (kg)	2.69	Power Factor (pf)	0.97
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	198-264
		Inrush Current Peak (A)	20.02
Light Output		Conductor Size (mm)	2.5
Lumens (lm)	5100	Terminal Type	3 pole piano key
Efficacy (lm/W)	121		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	3		
Driver			
Driver Current (mA)	1000mA		
Forward Voltage (V)	24-40		

Order Code: XCNC24NWHFS

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - Microwave Sensor - 4000K

Dimensions

A (mm)	1260
B (mm)	154
C (mm)	95

Line Drawing

