xcite LED Lighting

Data Sheet



Order Code: XCNC24NWM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Features



- · Available in 3 lengths
- Microwave movement sensor available
- Up to 121 lumens per watt efficacy

Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]

Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.

























Luminaire Wattage (W)	42
Weight (kg)	0.70
Operating Temperature (ta °C)	5 to 25
Light Output	
Lumens (Im)	5100
Efficacy (lm/W)	121
LED	
CCT (K)	4000
CRI	80
Macadam Elipses	3
Driver	
Driver Current (mA)	1000mA
Forward Voltage (V)	24-40

General

5100 121	Con
4000 80 3	
1000mA	

Emergency	
Emergency Lumen Operating	160
Emergency Wattage (W)	1

Electrical

Electrical	
Rated Input Current (A)	0.19
Power Factor (pf)	0.97
Input Voltage Range (VAC)	198-264
Inrush Current Peak (A)	20.02
Conductor Size (mm)	2.5
Terminal Type	4 pole piano key



xcite LED Lighting

Data Sheet



Order Code: XCNC24NWM3

42W - 1200mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1260
B (mm)	154
C (mm)	95

Line Drawing



