# xcite LED Lighting

## **Data Sheet**



0.34 0.98 198-264 39.52 2.5

4 pole piano key

### Order Code: XCNC26NWM3


77W - 1800mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

#### **Features**

- · Ideal for replacement of linear fluorescent fixtures
- · Available in 3 lengths
- Microwave movement sensor available
- Up to 123 lumens per watt efficacy

#### Construction

- Grey polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- CRI: Ra>80
- Supplied with neutral white [4000K]























## **Technical Data**

General		Electrical
Luminaire Wattage (W)	77	Rated Input Current (A)
Weight (kg)	4 28	Power Factor (pf)
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)
Light Output Lumens (Im)		Inrush Current Peak (A)
	9500	Conductor Size (mm)
Efficacy (lm/W)	123	Terminal Type
LED		
CCT (K)	4000	
CRI	80	
Macadam Elipses	3	
Driver		
Driver Current (mA)	1400mA	
Forward Voltage (V)	36-52	
Emergency		
Emergency Lumen Operating	160	
Emergency Wattage (W)	1	



# xcite LED Lighting

## **Data Sheet**



## Order Code: XCNC26NWM3

77W - 1800mm Twin Body Non Corrosive Polycarbonate Luminaire - IP65 - 3hrs Maintained Emergency - 4000K

### **Dimensions**

A (mm)	1830
B (mm)	158
C (mm)	102

## Line Drawing

