

Order Code: XCNC2X1

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [11W/13W/16W/18]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [emergency pack](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation

Technical Data

General		Electrical	
Luminaire Wattage (W)	11W/13W/16W/18	Rated Input Current (A)	0.06 to 0.09
Weight (kg)	0.83	Power Factor (pf)	0.86 to 0.93
Operating Temperature (ta °C)	-20° to +25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	20A
		Surge Protection (kV)	1
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	1600 - 2700		
Efficacy (lm/W)	151		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	6.7		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	42.7 to 45.6Vdc		

Order Code: XCNC2X1

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	675
B (mm)	95
B (mm)	80
Fix	400

Line Drawing

