

**Order Code: XCNC2X1MS**

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor



**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [11W/13W/16W/18]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

**Construction**

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [emergency pack](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

**Installation Notes**

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation



**Technical Data**

**General**

Luminaire Wattage (W)	11W/13W/16W/18
Weight (kg)	0.93
Operating Temperature (ta °C)	-20° to +25°

**Light Output**

Lumens (lm)	1600 - 2700
Efficacy (lm/W)	151

**LED**

CCT (K)	3000K/4000K/6000K
CRI	80
Macadam Elipses	6.7

**Driver**

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	42.7 to 45.6Vdc

**Electrical**

Rated Input Current (A)	0.06 to 0.09
Power Factor (pf)	0.86 to 0.93
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	20A
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3 pole piano key

**Order Code:** XCNC2X1MS

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

Dimensions

A (mm)	675
B (mm)	95
B (mm)	80
Fix	400

Line Drawing

