

Order Code: XCNC4X1

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [21W/26W/31W/36W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation

Technical Data

General

Luminaire Wattage (W)	21W/26W/31W/36W
Weight (kg)	1.57
Operating Temperature (ta °C)	5° to 25°

Light Output

Lumens (lm)	3500 to 5900
Efficacy (lm/W)	164

LED

CRI	80
Macadam Ellipses	7.6

Driver

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	91.7 to 99.1Vdc

Electrical

Rated Input Current (A)	0.1 to 0.17
Power Factor (pf)	0.93 to 0.97
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	190
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3 pole piano key

Order Code: XCNC4X1

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	1275
B (mm)	80
C (mm)	95
Fix	600

Line Drawing

