

Order Code: XCNC4X1M3MS

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [21W/26W/31W/36]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	21W/26W/31W/36	Rated Input Current (A)	0.1 to 0.17
Weight (kg)	2.27	Power Factor (pf)	0.93 to 0.97
Operating Temperature (ta °C)	+5° to +25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	32A
Light Output		Surge Protection (kV)	1
Lumens (lm)	3500 - 5900	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	164	Terminal Type	4 pole piano key
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	7.6		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	91.7 to 99.1Vdc		
Emergency			
Emergency Lumen Operating	327		
Emergency Wattage (W)	2		

Order Code: XCNC4X1M3MS

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

Dimensions

A (mm)	1275
B (mm)	95
B (mm)	80
Fix	600

Line Drawing

