# xcite LED Lighting

# **Data Sheet**



Order Code: XCNC4X1M3MS

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



#### **Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [21W/26W/31W/36W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

#### Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular microwave sensor for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

#### **Installation Notes**

Conduit and BESA fixing points for end or rear cable entry Loop in/out push-fit terminal block for quick installation





















### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	21W/26W/31W/36W	Rated Input Current (A)	0.1 to 0.17
Weight (kg)	2.27	Power Factor (pf)	0.93 to 0.97
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output  Lumens (Im)		Inrush Current Peak (A)	190
	3500 to 5900	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	164	Terminal Type	4 pole piano key
LED			
CRI	80		
Macadam Elipses	7.6		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	91.7 to 99.1Vdc		
Emergency			
Emergency Lumen Operating	327		
Emergency Wattage (W)	2		

# xcite LED Lighting

# **Data Sheet**



## Order Code: XCNC4X1M3MS

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

### **Dimensions**

A (mm)	1275
B (mm)	80
C (mm)	95
Fix	600

### Line Drawing



