

**Order Code: XCNC4X1MS**

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

**Technical Data****General**

Luminaire Wattage (W)	21W/26W/31W/36W
Weight (kg)	1.67
Operating Temperature (ta °C)	5° to 25°

**Light Output**

Lumens (lm)	3500 to 5900
Efficacy (lm/W)	164

**LED**

CRI	80
Macadam Ellipses	7.6

**Driver**

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	91.7 to 99.1Vdc

**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [21W/26W/31W/36W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

**Construction**

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

**Installation Notes**

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation

**Order Code: XCNC4X1MS**

1200mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

## Dimensions

A (mm)	1275
B (mm)	80
C (mm)	95
Fix	600

## Line Drawing

