

Order Code: XCNC5X1

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [29W/36W/43W/50]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [emergency pack](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	29W/36W/43W/50	Rated Input Current (A)	0.14 to 0.24
Weight (kg)	1.85	Power Factor (pf)	0.89 to 0.95
Operating Temperature (ta °C)	-20° to +25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	45A
Light Output		Surge Protection (kV)	1
Lumens (lm)	4700 - 7900	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	162	Terminal Type	3 pole piano key
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Elipses	6.5		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	124 to 134.1Vdc		

Order Code: XCNC5X1

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	1570
B (mm)	95
B (mm)	80
Fix	600

Line Drawing

