

Order Code: XCNC5X1

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [29W/36W/43W/50]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [emergency pack](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General

Luminaire Wattage (W)	29W/36W/43W/50
Weight (kg)	1.85
Operating Temperature (ta °C)	-20° to +25°

Light Output

Lumens (lm)	4700 - 7900
Efficacy (lm/W)	162

LED

CCT (K)	3000K/4000K/6000K
CRI	80
Macadam Elipses	6.5

Driver

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	124 to 134.1Vdc

Electrical

Rated Input Current (A)	0.14 to 0.24
Power Factor (pf)	0.89 to 0.95
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	45A
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3 pole piano key

Order Code: XCNC5X1

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	1570
B (mm)	95
B (mm)	80
Fix	600

Line Drawing

