

Order Code: XCNC5X1MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [29W/36W/43W/50W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular microwave sensor for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation

Technical Data**General**

| | |
|-------------------------------|-----------------|
| Luminaire Wattage (W) | 29W/36W/43W/50W |
| Weight (kg) | 1.95 |
| Operating Temperature (ta °C) | 5° to 25° |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 4700 to 7900 |
| Efficacy (lm/W) | 162 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.14 to 0.24 |
| Power Factor (pf) | 0.89 to 0.95 |
| Input Voltage Range (VAC) | 220 to 240 |
| Inrush Current Peak (A) | 200 |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 3 pole piano key |

LED

| | |
|------------------|-----|
| CRI | 80 |
| Macadam Ellipses | 6.5 |

Driver

| | |
|---------------------|--------------------|
| Driver Current (mA) | 200, 250, 300, 350 |
| Forward Voltage (V) | 124 to 134.1Vdc |

Order Code: XCNC5X1MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

Dimensions

| | |
|--------|------|
| A (mm) | 1570 |
| B (mm) | 80 |
| C (mm) | 95 |
| Fix | 600 |

Line Drawing

